

## DESCRIPTION

Johnstone's Trade Cleanable Matt is a tough premium matt emulsion which is designed to extend maintenance cycles with excellent stain resistant and high durability. Designed for high traffic areas which require frequent cleaning it helps to prevent stains setting into the paint and makes removing stains and marks easier.

## RECOMMENDED USES



Suitable for interior use on walls and ceilings.

## TYPE OF SUBSTRATE

Suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations. Also suitable for primed wood and metal.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Matt.

## VOLUME SOLID

38%

## COVERAGE



Approximately 15 square metres per litre depending on the nature and porosity of the surface.

## DRYING TIME



Touch dry in 1–2 hours.  
Recoat after 2–4 hours.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## THINNER

Clean water.

## VOC CONTENT

Low VOC content 0.30–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).  
This product contains max 10g/l VOC.

## FILM THICKNESS

Wet: 70µm, dry: 27µm.

## CLEANING STAINS

Apply all-purpose cleaner to sponge or soft cloth and wipe away stain from surface and allow to dry.

## KEY PROPERTIES

- Ideal for high traffic areas
- Stain resistant technology
- Extends maintenance cycles
- Class 1 Scrub rating ISO 11998

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

## APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces such as new plaster with a coat of Cleanable Matt thinned up to 20% with clean water. Ensure good ventilation during application and drying. Do not apply in temperatures below 10°C or in damp conditions.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1), octhilonone (ISO) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

## SIZES

5 Litre