

ш**е. 7500PF EBT**

BIODEGRADABLE, CHEMICAL RESISTANT, SINGLE USE GLOVE

100% biodegradable, single use glove engineered with Eco Best Technology®

FEATURES

- > 100% nitrile disposable glove with textured fingertips
- > Engineered with Eco Best Technology[®], making the glove biodegradable in biologically active landfills within 1-5 years
- > Non-sterile, silicone and latex free
- > Protects from a wide array of chemical hazards while avoiding type and type IV latex allergies
- > Low-modulus formulation to improve fit and reduce fatigue
- > Ambidextrous aiding the ability to easily put on and remove
- > AQL 1.0
- > Length: 240mm
- > Thickness: 0.10mm



Eco Best Technology

Showa's Eco Best Technology (EBT) is composed of organic material that accelerates the biodegradation of nitrile in biologically active landfills without anysacrifice in performance

SUITABLE FOR

Typical Industries

- Automotive
- Chemical
- Electronics
- Food
- Healthcare
- Laboratory
- Warehousing & Distribution

Suitable Applications

- Chemical Handling
- Food Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION







See overleaf for explanation

JKPT





RECOMMENDATIONS FOR USE

of entanglement

direct sunlight

suitable for its intended use

USE: Single use glove. Not suitable for thermal, electrical, heavy chemical protection. Do not use near moving machines if there is a risk

• STORAGE : Store in dry conditions in the original packaging and away from

 CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is

JAN 7500PF EBT

PRODUCT INFORMATION

MATERIALS	Nitrile with EBT [®]	
COLOUR	Blue	
LENGTH (mm)	240	
CUFF STYLE	Beaded	

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SHO75000 SHO75001 SHO75002 SHO75003 SHO75004 SHO75005	100 singles per box 10 boxes per case

CERTIFICATION LEGENDS

A R D

Е

E

G

н

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016 CODE CODE

M Ν

0

S

C	HEMICAL
N	lethanol
A	cetone
A	cetonitrile
D	ichloromethane
C	arbon Disulfide
T	oluene
D	iethylamine
T	etrahydrofurane
E	thyl acetate

CHEMICAL
n-Heptane
Sodium hydroxide 40%
Sulphuric acid 96%
65% Nitric acid
99% Acetic acid
25% Ammonium hydroxi
30% Hydrogen peroxide
40% Hydrofluoric acid

99% Acetic acid
25% Ammonium hydroxid
80% Hydrogen peroxide
10% Hydrofluoric acid
37% Formaldehyde

PE OF OVES	BREAKTHROUGH TIME
A	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least



PROTECTION AGAINST MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)



FOOD CONTACT DIRECTIVE 2002 / 72 EC

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- +44 (0)161 877 4747 T:
- +44 (0)161 877 4746 F:

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- +971 4 882 9962 T:
- F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2020 Globus (Shetland) Ltd | SHO-DATA-7500PF EBT-0620_1

EU compliance certificate delivered by the notified body SATRA Technology Europe, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (NB 2777) The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.