

B0979 - OREN TOP S3 SRC

Collection: Smart Evo

Upper: Suede leather and Technical Textile

Sole: Mono PU

Outer Carton: 10



Smart Evo

The lightweight and flexible range with minimalist style.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

EN ISO 20345:2011 S3 (SRC)

Features

- Shock absorption in the heel region
- Hydrocarbons resistant
- Puncture resistant sole
- Metal free
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Men's width
- Women's width
- Anti-static footwear
- 200 joules resistant toe-cap
- Water resistant upper
- SR - Slip Resistance Ceramic and Glycerin

B0979 - OREN TOP S3 SRC

Commodity Code:

Test House

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: N° F-113-04124-21

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	DUN14
B0979BGN36	Black/Green	67.0	41.0	36.0	0.4190	0.0989	8050262507801	88050262507807
B0979BGN37	Black/Green	67.0	41.0	36.0	0.4300	0.0989	8050262507818	88050262507814
B0979BGN38	Black/Green	67.0	41.0	36.0	0.4420	0.0989	8050262507825	88050262507821
B0979BGN39	Black/Green	67.0	57.0	36.0	0.4610	0.1375	8050262507832	68050262507834
B0979BGN40	Black/Green	67.0	57.0	36.0	0.4770	0.1375	8050262507849	68050262507841
B0979BGN41	Black/Green	67.0	57.0	36.0	0.4930	0.1375	8050262507856	68050262507858
B0979BGN42	Black/Green	67.0	57.0	36.0	0.5100	0.1375	8050262507863	68050262507865
B0979BGN43	Black/Green	67.0	57.0	36.0	0.5290	0.1375	8050262507870	68050262507872
B0979BGN44	Black/Green	67.0	57.0	36.0	0.5490	0.1375	8050262507887	68050262507889
B0979BGN45	Black/Green	67.0	57.0	36.0	0.5690	0.1375	8050262507894	68050262507896
B0979BGN46	Black/Green	67.0	57.0	36.0	0.5900	0.1375	8050262507900	68050262507902
B0979BGN47	Black/Green	67.0	57.0	36.0	0.6110	0.1375	8050262507917	68050262507919
B0979BGN48	Black/Green	67.0	57.0	36.0	0.6230	0.1375	8050262507924	68050262507926

