


# STYLE REF: PM4004

## STYLE NAME: AUSTIN




# Rock Fall®

INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 SRC | UK 3-16 (WHOLE SIZES) | COLOUR: BLACK

100% NON-METALLIC, WITH PROTECTIVE TOECAP AND MIDSOLE, AUSTIN IS LIGHTWEIGHT AND DEVELOPED WITH PREMIUM MATERIALS INCLUDING AN ACTIV-STEP® SHOCK ABSORBING DUAL DENSITY PU OUTSOLE AND ACTIV-STEP® PU ANTI-FATIGUE COMFORT FOOTBED.

# PM4004



### Upper Material

Water repellent smooth black leather

### Protective Components

Protective fibreglass toecap and composite anti-penetration flexi-midsole

### Lining Materials

Moisture wicking breathable mesh fabric lining

### Scuff Cap and Outsole

Activ-Step® shock absorbing PU outsole

### Footbed

Activ-Step® PU anti-fatigue comfort footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/03/2018

[WWW.ROCKFALL.COM](http://WWW.ROCKFALL.COM) | [WWW.ROCKFALL.COM/PRODUCTS/PM4004](http://WWW.ROCKFALL.COM/PRODUCTS/PM4004)

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

**EC DECLARATION OF CONFORMITY**



**Head Office & Distribution Centre**

Rock Fall UK Limited  
Unit 1 Major House  
Wimsey Way  
Alfreton, Derbyshire  
England. DE55 4LS

**E:** sales@rockfall.co.uk  
**T:** 01773 608616

[www.rockfall.co.uk](http://www.rockfall.co.uk)

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Declares that the PPE described hereafter;

**PRO-MAN PM4004**

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00367075** Issued by:-

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**


Signature:

Position: Director

Date: 18/04/2017



# EC Type Examination Certificate



## Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.  
Centre Court  
Meridian Business Park  
Leicester, LE19 1WD  
United Kingdom  
Phone: +44 (0)116 263 0330  
Fax: +44 (0)116 263 0311



[www.intertek.com](http://www.intertek.com)

<b>Issued to</b>	: RockFall UK Limited Major House, Wimsey Way, Alferton Trading Estate Alferton, Derbyshire DE55 4LS United Kingdom
<b>Date of Issue</b>	: 31 March 2017
<b>Expiry Date</b>	: 31 March 2022
<b>Certificate No.</b>	: LEC FI00367075
<b>Product Reference(s)</b>	: Pro-Man PM4004
<b>Description</b>	: Construction : Injection Toecap : Composite toe cap Midsole : Composite plate Last : 522 Sole : 17# Dual Density PU/PU sole Mould : 17# Test Report(s) : See technical file Size Range : 37-50 Category : S3 SRC

*P. Williamson*

Assessor

*M. Lutz*

Certification Manager


For and on behalf of ITS Testing Services (UK) Limited

31/03/2017

Date

31/03/2017

Date



Number: GZHT90408065

Tests Conducted (As Requested By The Applicant)

11 Slip Resistance (EN ISO 20344:2011(5.11), ISO 13287:2012, SRC, Temperature: 23°C)



I	(A)	Requirement	Pass/Fail
<u>Size 37</u> Left	On Eurotile 2 With NaLS		
	Forward Heel Slip (#1): 0.39	Min. 0.28	Pass
	Forward Flat Slip (#2): 0.39	Min. 0.32	Pass
	On Steel Floor With Glycerine		
<u>Size 42</u> Left	Forward Heel Slip (#1): 0.08	Min. 0.13	Fail
	Forward Flat Slip (#2): 0.11	Min. 0.18	Fail
	On Eurotile 2 With NaLS		
	Forward Heel Slip (#1): 0.39	Min. 0.28	Pass
<u>Size 50</u> Left	Forward Flat Slip (#2): 0.41	Min. 0.32	Pass
	On Steel Floor With Glycerine		
	Forward Heel Slip (#1): 0.08	Min. 0.13	Fail
	Forward Flat Slip (#2): 0.08	Min. 0.18	Fail
<u>Size 50</u> Left	On Eurotile 2 With NaLS		
	Forward Heel Slip (#1): 0.38	Min. 0.28	Pass
	Forward Flat Slip (#2): 0.36	Min. 0.32	Pass
	On Steel Floor With Glycerine		
<u>Size 50</u> Left	Forward Heel Slip (#1): 0.10	Min. 0.13	Fail
	Forward Flat Slip (#2): 0.17	Min. 0.18	Fail

Note:


It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark:

- #1 = Using Standard Shoemaking Last
- #2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.

Tests Conducted (As Requested By The Applicant)

1 Slip Resistance (EN ISO 20344:2011(5.11), ISO 13287:2012, SRB, Temperature: 23°C) 

			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 37</u>	Right	On Steel Floor With Glycerine		
		Forward Heel Slip (#1): 0.14	Min. 0.13	Pass
		Forward Flat Slip (#2): 0.18	Min. 0.18	Pass
<u>Size 42</u>	Right	On Steel Floor With Glycerine		
		Forward Heel Slip (#1): 0.14	Min. 0.13	Pass
		Forward Flat Slip (#2): 0.18	Min. 0.18	Pass
<u>Size 50</u>	Right	On Steel Floor With Glycerine		
		Forward Heel Slip (#1): 0.15	Min. 0.13	Pass
		Forward Flat Slip (#2): 0.19	Min. 0.18	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark:

#1 = Using Standard Shoemaking Last  
#2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.

---

*This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.*