

STYLE REF: PM600



Rock Fall®

INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 SRC | SIZE UK 3-13 (WHOLE SIZES) | COLOUR: BLACK

100% NON-METALLIC, ACTIV-STEP DUAL DENSITY OUTSOLE

PM600



CLICK A FEATURE OR COMPONENT TO LEARN MORE



100%
Non
Metallic



Anti
Static



Oil
Resistant



Protective
Midsole



Protective
Toecap



Small
Sizes
Available



Water
Repellent
Upper



SRC
Highest Level
Slip Resistance



Upper Materials

Smooth Leather

Outsole

Activ-Step Dual Density PU

Internal Toecap

Fibreglass

Lining Materials

Moisture wicking silver mesh

Footbed

EVA Footbed

Internal Midsole

Composite

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/03/2016

WWW.ROCKFALL.CO.UK | WWW.ROCKFALL.CO.UK/PRODUCTS/PM600

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

EC DECLARATION OF CONFORMITY



Head Office & Distribution Centre

Rock Fall UK Limited
Unit 1 Major House
Wimsey Way
Alfreton, Derbyshire
England. DE55 4LS

E: sales@rockfall.co.uk
T: 01773 608616

www.rockfall.co.uk

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Declares that the PPE described hereafter;

PRO-MAN PM600

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00332809** Issued by:-

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Signature:

Position: Director

Date: 01/01/2017



EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to : Rock Fall UK Limited
Major House, Wimsey Way, Alfreton Trading Estate, Alfreton,
Derbyshire DE55 4LS, United Kingdom

Manufacturer

Date of Issue : 14 May 2013

Expiry Date : 14 May 2018

Certificate No. : LEC FI00332809

Product Reference(s) : Pro-Man PM600 Fully Non-Metallic Boot

Description : Construction : Injection
Toecap : Composite Toecap
Midsole : Composite Insert Plate
Last : 459
Sole : 03# Dual Density PU/PU Sole
Mould : 03#
Test Report(s) : See Technical File
Size Range : 37 – 47
Category : S3 SRC



Assessor

14/05/2013

Date



Certification Manager

14/05/2013

Date

For and on behalf of **ITS Testing Services (UK) Limited**

Registered in England No. 1408264 Registered Office: 25 Savile Road, London W1S 2ES



Number: GZHT90250833

Tests Conducted (As Requested By The Applicant)

Outsole Slip Resistance (EN ISO 20344:2004/A1:2007 (5.18), SRA, 23°C):

			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 37</u>	<u>Ceramic Tile/Sodium Lauryl Sulphate</u>			
	Heel Part	0.38	Min. 0.28	Pass
	Flat Contact	0.39	Min. 0.32	Pass
<u>Size 42</u>	<u>Ceramic Tile/Sodium Lauryl Sulphate</u>			
	Heel Part	0.36	Min. 0.28	Pass
	Flat Contact	0.40	Min. 0.32	Pass
<u>Size 47</u>	<u>Ceramic Tile/Sodium Lauryl Sulphate</u>			
	Heel Part	0.38	Min. 0.28	Pass
	Flat Contact	0.43	Min. 0.32	Pass

Expanded Uncertainty: 0.01, With K=2.03 At 95% Confidence Level



Number: GZHT90333947

Tests Conducted (As Requested By The Applicant)

8 Slip Resistance (EN ISO 20344:2011(5.11), SRB, Temperature: 23°C)

	(B)	Requirement	Pass/Fail
<u>Size 37</u>	On Steel Floor With Glycerine		
	Forward Heel Slip (#1) 0.18	Min. 0.13	Pass
	Forward Flat Slip (#2) 0.24	Min. 0.18	Pass
<u>Size 42</u>	On Steel Floor With Glycerine		
	Forward Heel Slip (#1) 0.20	Min. 0.13	Pass
	Forward Flat Slip (#2) 0.25	Min. 0.18	Pass
<u>Size 47</u>	On Steel Floor With Glycerine		
	Forward Heel Slip (#1) 0.21	Min. 0.13	Pass
	Forward Flat Slip (#2) 0.26	Min. 0.18	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark:

- * = When Using Eurotile 2 For Footwear Testing, The Reported Footwear Test Result Shall Be The Coefficient Of Friction, CoF, Where $CoF = CoF_m - AF$.
 - CoF_m Is The Arithmetic Mean Of The Coefficients;
 - AF Is An Adjustment Factor As Follows:
 - 0.07 For Flat Test Mode;
 - 0.03 For The Heel Test Mode.

#1 = Using Standard Shoemaking Last

#2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With $k = 2.03$ At 95% Confidence Level.