


# STYLE REF: RFO01

## STYLE NAME: ALASKA



# Rock Fall®

INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 HI CI-40°C HRO SRC | SIZE UK 3-14 (WHOLE SIZES) | COLOUR: BLACK

ONE OF THE HIGHEST RATED COLD INSULATION BOOTS IN EUROPE, 100% NON-METALLIC, 3M THINSULATE

# RFO01



CLICK A FEATURE OR COMPONENT TO LEARN MORE



Anti Static



Cold Insulation



Heat Resistant to 300°C



Large Sizes Available



Oil Resistant



Protective Midsole



Protective Toecap



Small Sizes Available



Water Repellent Upper



Highest Level Slip Resistance

**3M**  
**Thinsulate**  
INSULATION

### Upper Materials

Supple Full Grain Leather – Anti Cracking

### Lining Materials

Thinsulate B600 Ultra +  
Breathable Mid-lining + Fursulate  
Fur Lining

### Outsole

Solid Nitrile Rubber –  
Temperature Resistant from –  
–40°C to +300°C

### Footbed

EVA Footbed

### Internal Toecap

Fibreglass

### Internal Midsole

Composite

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/03/2016

[WWW.ROCKFALL.CO.UK](http://WWW.ROCKFALL.CO.UK) | [WWW.ROCKFALL.CO.UK/PRODUCTS/ALASKA](http://WWW.ROCKFALL.CO.UK/PRODUCTS/ALASKA)

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

**EC DECLARATION OF CONFORMITY**



**Head Office & Distribution Centre**

Rock Fall UK Limited  
Unit 1 Major House  
Wimsey Way  
Alfreton, Derbyshire  
England. DE55 4LS

E: [sales@rockfall.co.uk](mailto:sales@rockfall.co.uk)  
T: 01773 608616

[www.rockfall.co.uk](http://www.rockfall.co.uk)

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Declares that the PPE described hereafter;

**ROCK FALL ALASKA RF001**

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00328914** Issued by:-

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**

Signature:

Position: Director

Date: 01/01/2017



# EC Type Examination Certificate



## Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.  
Centre Court  
Meridian Business Park  
Leicester, LE19 1WD  
United Kingdom  
Phone: +44 (0)116 263 0330  
Fax: +44 (0)116 263 0311



[www.intertek.com](http://www.intertek.com)

**Issued to** : Rockfall UK Ltd  
Wimsey Way, Alfreton Trading Estate, Derbyshire, UK  
DE55 4LS

**Manufacturer**

**Date of Issue** : 19 November 2012

**Expiry Date** : 19 November 2017

**Certificate No.** : LEC FI00328914

**Product Reference(s)** : RF001 ALASKA

**Description**

Construction	:	Cemented
Toecap	:	PEP# Composite
Midsole	:	PEP# Composite
Last	:	#PEP-PL
Sole	:	PS-2061 RB
Test Report(s)	:	See Technical File
Size Range	:	5 – 13
Category	:	S3 HRO CI SRC

  
Assessor

19/11/2012

Date



Certification Manager

19/11/2012

Date


For and on behalf of **ITS Testing Services (UK) Limited**

Registered in England No. 1408264 Registered Office: 25 Savile Road, London W1S 2ES



**Test Report**

Tests Conducted (As Requested By The Applicant)



Number: GZHT90492559

Slip Resistance (EN ISO 20344:2011(5.11) & ISO 13287:2012, SRA, Temperature: 23°C)

			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 36</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.33	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.34	Min. 0.32	Pass
<u>Size 42</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.34	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.35	Min. 0.32	Pass
<u>Size 47</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.35	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.35	Min. 0.32	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark:

- #1 = Using Standard Shoemaking Last
- #2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.

---

*This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.*



中国认可  
国际互认  
检测  
TESTING  
CNAS L0220

Number: GZHT90593751

**Test Report**

Tests Conducted (As Requested By The Applicant)

6 Slip Resistance (EN ISO 20344:2011(5.11) & ISO 13287:2012, SRB, Temperature: 23°C)

Sample	Size	Test Floor	Lubricant	Modes	Results	Requirement	Pass/Fail
-	36 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.16	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.23	Min. 0.18	Pass
	42 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.18	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.23	Min. 0.18	Pass
	47 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.19	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.25	Min. 0.18	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark: #1 = Using Standard Shoemaking Last  
#2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.





Number: GZHT90260402

Tests Conducted (As Requested By The Applicant)

Cold Insulation Of Sole Complex (Completed Footwear) (EN ISO 20344: 2004 /A1:2007(5.13), Modified, -40°C):

	<u>Suggestion</u>	<u>Pass/Fail</u>
	<u>Requirement</u>	
Right:	*	Pass
8.5°C Temperature		
Decrease And The		
Insulation Incorporated		
In The Footwear That It		
Cannot Be Removed		
Without Damaging The		
Footwear		

Remark: \* = Max. 10 °C Temperature Decrease On The Upper Surface Of The Insole, The Insulation Shall Be Incorporated In The Footwear In Such A Manner That It Cannot Be Removed Without Damaging The Footwear

Expanded Uncertainty: 1.10°C, With K = 2.12 At 95% Confidence Level



Number: GZHT90260402

Tests Conducted (As Requested By The Applicant)

