


STYLE REF: VX500

STYLE NAME: EMERALD



Rock Fall®

INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 SRC | SIZE UK 2-8 (WHOLE SIZES) | COLOUR: BLACK

DESIGNED TO FIT A LADIES FOOT, SOFT PADDED TONGUE AND COLLAR, DUAL DENSITY PU OUTSOLE

VX500



CLICK A FEATURE OR COMPONENT TO LEARN MORE



Anti Static



Oil Resistant



Protective Midsole



Protective Toecap



Water Repellent Upper



Small Sizes Available



Ladies Fit



Highest Level Slip Resistance

Upper Materials

Full Grain Leather

Outsole

Dual Density PU

Internal Toecap

Steel

Lining Materials

Breathable Fabric

Footbed

EVA Footbed

Internal Midsole

Composite

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/01/2016

WWW.ROCKFALL.CO.UK | WWW.ROCKFALL.CO.UK/PRODUCTS/EMERALD

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

EC DECLARATION OF CONFORMITY



Head Office & Distribution Centre

Rock Fall UK Limited
Unit 1 Major House
Wimsey Way
Alfreton, Derbyshire
England. DE55 4LS

E: sales@rockfall.co.uk
T: 01773 608616

www.rockfall.co.uk

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Declares that the PPE described hereafter;

VIXEN EMERALD VX500

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00339196** Issued by:-

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD
CENTRE COURT
MERIDIAN BUSINESS PARK
LEICESTER
LE19 1WD**


Signature:

Position: Director

Date: 01/01/2017



EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to : Rock Fall Uk Ltd
Major House, Unit 1 Wimsey Way, Alfreton, Derbyshire,
United Kingdom DE55 4LS

Manufacturer

Date of Issue : 22 January 2014

Expiry Date : 22 January 2019

Certificate No. : LEC FI00339196

Product Reference(s) : VX400 (FM1105), VX530 (FM1107), VX500 (FM1205),
VX540 (FM1106)

Description	:	Construction	:	Injection
		Toecap	:	Steel
		Midsole	:	Composite
		Last	:	JT021S
		Sole	:	PU Injection
		Mould	:	JT-021 PU Injection
		Test Report(s)	:	See Technical File
		Size Range	:	35 – 42
		Category	:	S3 SRC

Assessor

22/01/2014

Date

Certification Manager

22/01/2014

Date

For and on behalf of **ITS Testing Services (UK) Limited**

Registered In England No. 1408264 Registered Office: Academy Place, 1-9 Brook Street, Brentwood, Essex. CM14 5NQ

Tests Conducted (As Requested By The Applicant)

10 Slip Resistance (EN ISO 20344:2011(5.11), ISO 13287:2012, SRC, Temperature: 23°C)

		(A)	Requirement	Pass/Fail
Size 35	Left	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.48	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.46	Min. 0.32	Pass
		On Steel Floor With Glycerine		
Size 42	Right	Forward Heel Slip (#1): 0.17	Min. 0.13	Pass
		Forward Flat Slip (#2): 0.24	Min. 0.18	Pass
		On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.51	Min. 0.28	Pass
Size 42	Right	Forward Flat Slip (#2): 0.47	Min. 0.32	Pass
		On Steel Floor With Glycerine		
		Forward Heel Slip (#1): 0.19	Min. 0.13	Pass
		Forward Flat Slip (#2): 0.21	Min. 0.18	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark:

#1 = Using Standard Shoemaking Last

#2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.