

Tork Flushable Singlefold Hand Towel

Advanced

290190



Description

Satisfy hand drying needs with the Advanced Tork Singlefold Hand Towels ensure the right quality for when cost and performance are equally important. These towels are suitable for the Tork Singlefold Hand Towel Dispenser for demanding environments. Help control consumption and promote good hygiene with reliable one-at-a-time dispensing.

- Attractive Tork Leaf décor: designed to make a great impression
- Flushable hand towel ideal for high risk areas where towels may be put in the toilet instead of the waste bin
- One-at-a-time dispensing for reduced consumption and increased hygiene

Certifications



For Wiping

Product Details

System	H3
Color	White
Folding type	Singlefold
Print	No
Unfolded Width	22.5 cm
Folded width	22.5 cm
Embossing	Yes
Pulp Quality Indicator	3
Folded length	11.5 cm
Ply	2
Total Grammage	44 g
Unfolded length	23 cm
Roll/Piece Net Weight	2.26 g
Fibre Type	Virgin
Roll Gross Weight	2.29 g

Shipping Data

	Consumer Units (CON)	Transport unit (TRP)	Pallet (PAL)
EAN	7322540569353	7322540569360	7322540750737
Packaging Material	Banderole	Carton	-
Pieces	250	3750 (15 CON)	93750 (25 TRP)
Height	130 mm	242 mm	1,371 mm
Length	115 mm	596 mm	1,200 mm
Width	230 mm	406 mm	1,000 mm
Gross Weight	573.4 g	9.31 kg	232.72 kg
Net Weight	565.7 g	8.49 kg	212.14 kg
Volume	3.44 dm3	58.56 dm3	1.46 m3
Layers Per Pallet	-	-	5
TRP Per Layer	-	-	5

Compatible Products



Tork Singlefold HT Disp Metal White
208140



Tork Singlefold Hand Towel Disp White
553000



Tork Mini Singlefold HT Disp White
553100



Tork Mini Singlefold HT Disp Black
553108

Environmental Information

Content

The product is made from

Fresh fibres

The packaging material is made from paper or plastic.

Material

Fresh fibres

Essity has an ambitious target that all raw materials derived from wood-based fresh fibre used in the production of our products is certified either in accordance with the FSC® or the Program for the Endorsement of Forest Certification (PEFC™). In addition, all wood-based fresh fibre shall fulfil the FSC® Controlled Wood standard, including third-party verification. The Essity Fibre Sourcing Policy describes this in more detail and can be found on www.essity.com.

Fresh fibre pulp is produced from softwood or hardwood. The wood is subject to chemical and /or mechanical processes where the cellulose fibres are separated out and lignin and other residuals are removed.

Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety.

Chemicals

All chemicals (process aids as well as additives) are assessed from an environmental, occupational health and safety and product safety point of view.

To control product performance we use additives:

- Wet strength agents (for Wipers and Hand Towels)
- Dry strength agents (are used together with mechanical treatment of the pulp to make strong products like wipers)
- For coloured papers dyes and fixatives (to secure perfect fastness of the colour) are added
- For printing products printing inks (pigments with carriers and fixatives) are applied
- For multi ply products we often use water soluble glue to secure the integrity of the product

In most of our mills we do not add optical brighteners.

We do not use softeners for professional hygiene products.

High product quality is secured through quality and hygiene management systems throughout production, storage and transport.

In order to maintain a stable process and product quality the paper manufacturing process is supported by the following chemicals/ process aids:

Tork Flushable Singlefold Hand Towel

Advanced

290190

- defoamers (surfactants and dispersing agents)
- pH-control (sodium hydroxide and sulphuric acid)
- retention aids (chemicals that help to agglomerate small fibres to prevent fibre loss)
- Coating chemicals (that help to control the creping of the paper to make it soft and absorbent)

To reuse broke we use:

- Pulping aid (chemicals that help to repulp wet strong paper)

In the cleaning of our waste water we use flocculation agents and nutrients for the biological treatment to secure that no negative impact on water quality comes from our mills.

Food Contact

This product fulfills the legislative requirements for Food Contact materials, confirmed by external certification performed by a third party. The product is safe for wiping food contact surfaces and may also come occasionally into contact with foodstuffs for a short period of time.

Environmental certification

This product is certified with the EU Ecolabel with certificate number SE/004/001.

This product is certified for FSC® with certificate number SA-COC-008266.

Packaging

Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes

Article creation date and latest article revision

Date of issue: 19-04-2019

Revision date: 21-05-2026

Production

This product is produced at Kostheim - DE mill and certified according to HACCP, ISO 9001, ISO 14001 (Environmental management systems), EMAS (eco-management and audit scheme), ISO 45001, ISO 50001 and FSC Chain-Of-Custody.

Destruction

This product is mainly used for personal hygiene and can be collected together with household waste.

Essity UK Ltd, Southfields Road, Dunstable, Bedfordshire LU6 3EJ, United Kingdom