

* High Traffic Floor Polish

21% Solids

Jangro *

BD019-5



Floor Polishing:



1 Place safety Sign & use the appropriate PPE as indicated in the Safety Data Sheet.




2 Prepare the floor, remove all traces of old polish/sealer. Ensure floor is clean dry and neutral*.




3 Pour polish into bucket or tray (undiluted).




4 Place flat mop or applicator into polish. Remove surplus.




5 Apply polish to dry floor, thinly and evenly in straight lines.



6 Leave to dry thoroughly. Approximately 1 hour.



7 Ensure floor is free from debris/dust before applying a second coat. Apply in opposite direction to the first. Leave a 2.5-5cm gap from the edge.



8 Leave to dry. Light traffic 4-8 hours, heavy traffic 24-48 hours. A third coat may be required on old worn floors.



9 For best results, maintain with Jangro Perfumed Floor Maintainer. BD030-5.



10 Remove Safety Signs.

*Refer to the Jangro Floor Care Chart or the product Usage Guide for Floor Polish Remover for guidance on floor preparation.

Areas for use



Scan QR code for further product details

Health & Safety

Please refer to relevant COSHH Safety Data Sheet

www.jangro.net



Avoid contact with eyes.
If contact occurs, rinse immediately with clean water.

Product Usage Guide

Professional