



SAFETY DATA SHEET

Jangro - ACRYLIC FLOOR PRIMER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Jangro - ACRYLIC FLOOR PRIMER
Product number	A061 JA
Internal identification	BD125-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Aqueous Floor Seal.
-----------------	---------------------

1.3. Details of the supplier of the safety data sheet

Supplier

Jangro Limited
Jangro House
Worsley Road
Farnworth
Bolton. UK
BL4 9LU
Tel: 01204 795 955
Fax: 01204 579 499
enquiries@jangrohq.net

1.4. Emergency telephone number

Emergency telephone	01772 318 818 - 8.30am to 4.45pm - Mon to Fri
---------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified

2.2. Label elements

Hazard statements	EUH208 Contains 1,2-BENZISOTHIAZOLIN-3-ONE. May produce an allergic reaction.
Precautionary statements	P102 Keep out of reach of children. P301 IF SWALLOWED: P313 Get medical advice/ attention. P501 Dispose of contents/ container in accordance with local regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Jangro - ACRYLIC FLOOR PRIMER

ALCOHOL (C9-C11) ETHOXYLATE (6EO) 0.1-1% CAS number: 68439-46-3 Alternative CAS No 68439-45-2
Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318
1,2-BENZISOTHAZOLIN-3-ONE <0.1% CAS number: 2634-33-5 EC number: 220-120-9 M factor (Acute) = 1 Spec Conc Limits :- Skin Sens. 1; H317 ≥ 0.05% EUH208 ≥ 0.005%
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The ingredients are present in non-hazardous concentrations.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Do not induce vomiting. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Wash with plenty of water.
Eye contact	Rinse immediately with plenty of water. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known. But - May cause discomfort if swallowed.
Skin contact	No specific symptoms known. But prolonged or excessively repeated skin contact could lead to removal of natural oils from skin.
Eye contact	No specific symptoms known. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Jangro - ACRYLIC FLOOR PRIMER

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances:
Irritating gases or vapours.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No special protective clothing. (See Sec 8)

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Small Spillages: Flush away spillage with plenty of water. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions No specific recommendations.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container in a cool, well-ventilated place. Store away from the following materials: Oxidising materials.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description See Product Information Sheet & Label for detailed use of this product.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

2-(2-BUTOXYETHOXY)ETHANOL

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67,5 mg/m³

Short-term exposure limit (15-minute): WEL 15 ppm 101,2 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering controls Not relevant.

Eye/face protection No specific eye protection required during normal use.

Jangro - ACRYLIC FLOOR PRIMER

Hand protection	No specific hand protection recommended. For prolonged or repeated skin contact use suitable protective gloves.
Other skin and body protection	None required.
Respiratory protection	Respiratory protection not required.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Emulsion.
Colour	White.
Odour	Acrylic
pH	pH (concentrated solution): 7.60
Melting point	-1°C
Initial boiling point and range	101°C @ 760 mm Hg
Flash point	Boils without flashing.
Relative density	1.020 @ 20°C
Solubility(ies)	Soluble in water.

9.2. Other information

Other information	None.
--------------------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	No particular stability concerns.
------------------	-----------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	See sections 10.1,10.4 & 10.5
---	-------------------------------

10.4. Conditions to avoid

Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	No known hazardous decomposition products.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Jangro - ACRYLIC FLOOR PRIMER

Toxicological effects We have not carried out any animal testing for this product. Any ATE figures quoted below are from Toxicity Classifications that have been carried out using ATE (Acute Toxicity Estimate) Calculation Method using LD50 or ATE figures provided by the Raw Material Manufacturer.

Other health effects Low oral toxicity, but ingestion may cause irritation of the gastro-intestinal tract.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity We have not carried out any Aquatic testing, therefore we have no Aquatic Toxicity Data specifically for this product. The Aquatic Toxicity Data, where provided by the raw material manufacturer for ingredients with aquatic toxicity, can be made available on request.

12.2. Persistence and degradability

Persistence and degradability The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Small amounts (less than 5 Litres) of unwanted product may be flushed with water to sewer. Larger volumes must be sent for disposal by approved waste contractor. Consign empty container to normal waste.

SECTION 14: Transport information

General Not classified for Transport.

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Jangro - ACRYLIC FLOOR PRIMER

EU legislation Safety Data Sheet prepared in accordance with REACH Commission Regulation (EU) No 2015/830 (which amends Regulation (EC) No 453/2010 & 1907/2006).
The product is as classified under GHS/CLP- Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures.
Ingredients are listed with classification under GHS/CLP - Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out as not applicable as this product is a mixture.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.
ATE: Acute Toxicity Estimate.
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
GHS: Globally Harmonized System.
Spec Conc Limits = Specific Concentration Limits.

Classification abbreviations and acronyms Acute Tox. = Acute toxicity
Aquatic Acute = Hazardous to the aquatic environment (acute)
Eye Dam. = Serious eye damage
Skin Irrit. = Skin irritation
Skin Sens. = Skin sensitisation

Key literature references and sources for data Material Safety Data Sheet, Miscellaneous manufacturers. CLP Class - Table 3.1 List of harmonised classification and labeling of hazardous substances. ECHA - C&L Inventory database.

Classification procedures according to Regulation (EC) 1272/2008 Calculation Method.

Revision comments Addition of EUH208 (changes to sections 2,3 & 16) & Safety Data Sheet amended in accordance with REACH Commission Regulation (EU) No 2015/830 amendment. (Changes to Sections 2,3,15&16)

Revision date 01/08/2017

Revision 6

SDS status The Hazard Statements listed below in this Section No 16 relate to the Raw Materials (Ingredients) in the Product (as listed in Section 3) and NOT the product itself. For the Hazard Statements relating to this Product see Section 2.

Hazard statements in full H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
EUH208 Contains 1,2-BENZISOTHIAZOLIN-3-ONE. May produce an allergic reaction.