

Jersette 301

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 29-33
- **Thickness (mm)** 1.15
- **Wrist** Scalloped cuff
- **Colour/Color** Blue
- **Interior finish** Textile support
- **Exterior finish** Pebbled
- **Size / EAN** 5 6 7 8 9 10
- **Packaging** 1 pair/bag - 5 pairs/bag - 50 pairs/carton
- **Complementary information** Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 2



X1XXXX



3141

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Abrasion resistance
 └─ Blade cut resistance
 └─ Tear resistance
 └─ Puncture resistance



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374



RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Burning behaviour
 └─ Contact heat resistance
 └─ Convective heat resistance
 └─ Radiant heat resistant
 └─ Resistance to small drops of molten metal
 └─ Resistance to large quantities of molten metal



SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Convective cold resistance
 └─ Contact cold resistance
 └─ Water permeability

For more details: www.mapa-pro.com

SPECIFIC ADVANTAGES

- Freedom of movement, due to the anatomical shape and excellent comfort from the seamless textile support
- Good tear-resistance
- Good resistance to many diluted acids and bases

MAIN FIELDS OF USE

Construction Industry (Masons / Plasterers)

- Preparing and pouring mortar and cement

Aeronautics industry

- Work with composite materials (resins)

Local Authorities (Cleaning)

- Handling household detergents

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with a solvent (alcohol, etc...) : rub over with a dry cloth
- in use with detergents, acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : inappropriate usage of the gloves or submitting them to a cleaning or laundering process which is not specifically recommended, can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0072/014/162/09/94/001 EX 01/09/94

- Issued by the notified body nr

0072

I.F.T.H. – Av. Guy de Collongue F-69134 ECULLY CEDEX