

# Vital 117

## DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 30,5
- **Thickness (mm)** 0.35
- **Wrist** Straight cuff
- **Colour/Color** Blue
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton



## PERFORMANCE RESULTS

Certification category 3

CE 0334



1010

### Legends



**MECHANICAL HAZARDS**  
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4  
 └─ Puncture resistance  
 └─ Tear resistance  
 └─ Blade cut resistance  
 └─ Abrasion resistance



**LOW CHEMICAL PROTECTION**  
EN 374



**MICRO-ORGANISMS**  
EN 374



**RADIOACTIVE CONTAMINATION**  
EN 421



**HEAT AND FIRE**  
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4  
 └─ Resistance to large quantities of molten metal  
 └─ Resistance to small drops of molten metal  
 └─ Radiant heat resistant  
 └─ Convective heat resistance  
 └─ Contact heat resistance  
 └─ Burning behaviour



**SPECIFIC CHEMICAL PROTECTION**  
EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS**  
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1  
 └─ Water permeability  
 └─ Contact cold resistance  
 └─ Convective cold resistance

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**SPECIFIC ADVANTAGES**

- Excellent dexterity from the suppleness of natural latex
- Good resistance
- Comfortable cotton flock-lining

**MAIN FIELDS OF USE****Mechanical industry**

- Assembly of small, oil and grease free parts

**Local Authorities (Cleaning)**

- Handling household detergents

**INSTRUCTIONS FOR USE****Instructions for use**

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitised to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website [www.mapa-pro.com](http://www.mapa-pro.com) or contact the Technical Customer Service - MAPA PROFESSIONNEL ([stc.mapaspontex@mapaspontex.fr](mailto:stc.mapaspontex@mapaspontex.fr)) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

**Storage conditions**

Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

**Laundering conditions**

Before taking off the gloves, clean them as appropriate :

- in use with a solvent (alcohol, etc...) : rub over with a dry cloth
- in use with detergents, acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : using the gloves or submitting them to another cleaning or laundering process can alter their performance levels.

**Drying conditions**

Ensure the inside of the gloves is dry before putting them on again.

**LEGISLATION**

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/09/09/0406 Ext 01/09/09

- Issued by the notified body nr

0075

C.T.C - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France

- Quality assurance certificat

0334 Asqual 14 rue des Reculettes -F-75013 PARIS