

SPECIFICATION SHEET



TITAN II VW256.01

Safety Specification
EN ISO 20345:2011 S5 SRA



ANTI-SLIP
TRACTION



ANTI-STATIC



STEEL
MIDSOLE



STEEL
TOECAP

Size

Size 3 – 13 (36 – 48)

Weight

1,115g
based on a size 8 (42)

Description

- A durable safety wellington with a redesigned comfort toecap and protective midsole
- Slip-safety assured with a high-performing slip-resistant tread
- Comfort and durability from a flexible PVC and Nitrile Rubber construction
- Feet given further protection as Titan II is resistant to several contaminants
- Additional safety with a reinforced lower shin protector and reflective trim for visibility

Toecap

Feet are kept safe and comfortable with a redesigned generous-fit corrosion-resistant steel toecap, tested to impact of 200J.

Protective midsole

Feet are kept safe from sharp items entering underfoot with a flexible corrosion and pierce-resistant steel midsole, tested to 1100N.

Sole

Slip safety is assured through a reinforced red PVC/Nitrile rubber sole, redesigned with a tread pattern to ensure excellent grip on wet and muddy terrain.

Upper

Superb protection given with Titan's black rubber upper, designed with thick reinforced mouldings around the edge of the foot, lower shin and ankle. Further comfort is provided with internal trouser grips.

Footbed

Long-lasting comfort for the wearer with a breathable foam footbed featuring a padded arch guard and a durable polyester top cover.

Lining

Long-lasting comfort with a durable polyester lining.

Warranty

We're so confident that our boots will stand the test of time, we offer a 200-day guarantee.

EN ISO 20345:2011 standards for general purpose safety footwear.

Features	Test Performed	Safety Classifications				
		S1	S2	S3	SBP	S1P
SB	Toe protection tested with 200J impact and 15kN compression force	✓	✓	✓	✓	✓
P	Penetration-resistant outsole tested at 1100N			✓	✓	✓
A	Electrical resistance between foot and ground of between 0.1 and 1000 mega ohms	✓	✓	✓		✓
E	Energy absorption of the seat region tested at 20 joules	✓	✓	✓		✓
WRU	Water-resistant upper leather			✓	✓	

Additional test classifications

HRO	Heat-resistant outsole compound tested at 300°C
CI	Insulation against the cold - temperature drops less than 10°C when tested at -17°C
M	Metatarsal protection - tested to 100J impact
SRA	Slip-resistant on ceramic tile floor with sodium lauryl sulphate solution
SRB	Slip-resistant on steel floor with glycerol
SRC	Slip-resistant for both SRA and SRB

FOOT HEALTH

For foot health advice, scan the QR code.



BOOT CARE

For boot care advice, scan the QR code.



If you're unsure if these are the right boots for you and your environment, head to our boot finder by scanning the QR code and we'll give you our expert recommendations from the V12 range.

sales@V12footwear.com
+44 (0)1249 651 900
V12footwear.com