SAFETY DATA SHEET

FABRIC UPHOLSTERY CLEANER

Issued: 23/08/2005

Revision No: 2

Page 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: FABRIC UPHOLSTERY CLEANER

Synonyms: FABRIC CLEANER

FCL

Use / description of product: Extremely flammable.

Company name: Specialised Aerosols Company Limited

Carr Green Lane Mapplewell Barnsley

South Yorkshire

S75 6DY

Tel: 01226 387101 Fax: 01226 387100

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: PHOSPHATE ESTER <1%

CAS: 72283-31-9 [Xi] R36/38

• SODIUM ALKYETHER SULPHATE <1%

[Xi] R36/38

• ALCOHOL ETHOXYLATE WITH 6.5MEO 95.000% 1-10%

CAS: 68439-45-2 [Xn] R22; [Xi] R41

• BUTANE 1-10%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

• PRIMARY ALCOHOL ETHOXYLATE 1-10%

[Xn] R22; [Xi] R41

• SODIUM HYDROXIDE <1%

EINECS: 215-185-5 CAS: 1310-73-2

[C] R35

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Issued: 23/08/2005

SAFETY DATA SHEET

FABRIC UPHOLSTERY CLEANER

Page 2

Ingestion: Nausea and stomach pain may occur. There may be vomiting. Inhalation of fumes from the

stomach may cause symptoms similar to direct inhalation.

Inhalation: Nausea and stomach pain may occur. There may be vomiting. Drowsiness or mental confusion

may occur. There may be loss of consciousness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to

hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. If

unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious,

check for breathing and apply artificial respiration if necessary. If unconscious and breathing is

OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to

hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide.

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Vapour may travel considerable distance

to source of ignition and flash back. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access

to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method. Wash the spillage site with large amounts of water. Do not use

equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly

closed.

Issued: 23/08/2005

SAFETY DATA SHEET

FABRIC UPHOLSTERY CLEANER

Page 3

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: BUTANE

TWA 1450 mg/m3 STEL 1810 mg/m3

• SODIUM HYDROXIDE

STEL 2 mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.Eye protection: Safety goggles.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol
Colour: Typical.

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Flammability limits %: lower: 0.8

upper: 9.0

Flash point°C: -10

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Sources of ignition. Heat. Flames.

Materials to avoid: Strong oxidising agents. Strong alkalis. Mineral Acids.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: SODIUM HYDROXIDE

IPR MUS LD50 40 mg/kg ORL RBT LDLO 500 mg/kg

Chronic toxicity: Inhalation. Skin and/or eye contact.

Routes of exposure: May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness

and nausea. Prolonged inhalation of high concentrations may damage respiratory system. May

cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. Prolonged or repeated exposure may cause severe

iritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating

to eyes. May cause chemical eye burns.

Issued: 23/08/2005

SAFETY DATA SHEET

FABRIC UPHOLSTERY CLEANER

Page 4

12. ECOLOGICAL INFORMATION

Other adverse effects: Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Empty containers must not be burned because of explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950 **ADR Class:** 2

Shipping name: AEROSOLS

Labelling: 2.1



IMDG / IMO

UN no: 1950 Class: 2

EmS: F-D,S-U **Marine pollutant:** .

Labelling: 2.1

IATA / ICAO

UN no: 1950 Class: 2

Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.



Risk phrases: R12: Extremely flammable.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding

50°C. Do not pierce or burn, even after use.

SAFETY DATA SHEET

FABRIC UPHOLSTERY CLEANER

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R36/38: Irritating to eyes and skin.

R22: Harmful if swallowed.

R41: Risk of serious damage to eyes.

R12: Extremely flammable.

R35: Causes severe burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.