

FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Page: 1

Compilation date: 27/06/2005

Revision date: 23/01/2018

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Product code: FGSS500

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Specialised Aerosols Company Limited

Carr Green Lane

Mapplewell

Barnsley

South Yorkshire

S75 6DY

Tel: 01226 387101

Fax: 01226 387100

Email: sales@specialised-aerosols.co.uk

1.4. Emergency telephone number

Emergency tel: 07836317118

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222

Most important adverse effects: Extremely flammable aerosol.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

Hazard pictograms: GHS02: Flame



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Page: 2

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P501: Dispose of contents/container to hazardous or special waste collection point.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BUTANE

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|---------------|-----|--|-------------------------------------|---------|
| 203-448-7 106 | | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | |

KEROSINE - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

| 265-149-8 | 64742-47-8 | - | Asp. Tox. 1: H304; Aquatic Chronic 2: | |
|-----------|------------|---|---------------------------------------|--|
| | | | H411 | |

ISOBUTANE

| 200-857-2 | 75-28-5 | Substance with a Community | Flam. Gas 1: H220; Press. Gas: H280 | 1-10% |
|-----------|---------|----------------------------|-------------------------------------|-------|
| | | workplace exposure limit. | | |

Contains: We can confirm that this product does not contain any of the 14 allergens as listed in Annex II of the EU Food Information for Consumers Regulation No. 1169/2011 and Commission Delegated Regulation (EU) No. 78/2014

amending Annex II to Regulation (EU) No 1169/2011 (statement verified January 2018)

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Get medical attention if any discomfort

continues.

Eye contact: Make sure contact lenses are removed from eyes before washing. Promptly wash eyes with

plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical $\frac{1}{2}$

attention if any discomfort continues.

Ingestion: Do not induce vomiting. Rinse mouth thoroughly with water and give large amounts of milk or

water to people not unconscious. Get medical attention if any discomfort continues.

Inhalation: Remove the patient to fresh air. When breathing is difficult, properly trained personnel may

assist affected person by administering oxygen. Keep the affected person warm and at rest.

Get prompt medical attention.

FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on

skin. May cause cracking of skin, and eczema.

Eye contact: Irritating to eyes. May cause chemical eye burns.

Ingestion: May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal

symptoms, including upset stomach.

Inhalation: May cause irritation to the respiratory system. Vapours may cause headache, fatigue.

dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory

system.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: NOTE: Effects may be delayed. Keep affected person under observation.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Use powder, foam, sand or water spray.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Aerosol cans may explode in fires.

5.3. Advice for fire-fighters

Advice for fire-fighters: Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapours

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up

to prevent the escape of liquid. Mark out the contaminated area with signs and prevent

access to unauthorised personnel.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames,

heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of

explosion risk. If leaking cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Page: 4

7.1. Precautions for safe handling

Handling requirements: Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use

approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50C.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTANE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------|--------------|------------|--------------|
| UK | 1450 mg/m3 | 1810 mg/m3 | - | - |

ISOBUTANE

| UK | 2400 mg/m3 | 9600 mg/m3 | - | - |
|----|------------|------------|---|---|
|----|------------|------------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Provide adequate general and local exhaust ventilation.

Respiratory protection: No specific recommendations made, but repiratory protection must be used if the general

level exceeds the Occupational Exposure Level (OEL). Use chemical cartridge protection

with appropriate cartridge.

Hand protection: Protective gloves.

Eye protection: Wear approved chemical safety goggles where eye exposure is reasonably probable.

Skin protection: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Environmental: DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before

eating, smoking and using the toilet. Promptly remove any clothing that becomes

contaminated. When using do not eat, drink or smoke.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol Colour: Typical.

FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Page: 5

Odour: Characteristic odour

Flammability limits %: lower: 0.8 upper: 9.0

Flash point°C: -10

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No specific reactivity hazards associated with this product.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Not known.

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong alkalis.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on

skin. May cause cracking of skin, and eczema.

Eye contact: Irritating to eyes. May cause chemical eye burns.

Ingestion: May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal

symptoms, including upset stomach.

Inhalation: May cause irritation to the respiratory system. Vapours may cause headache, fatigue.

dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory

system.

Other information: Route of entry: Inhalation. Skin and /or eye contact.

Section 12: Ecological information

FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Page: 6

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Dangerous for the environment if discharged into watercourses.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Empty containers must not be burned because of explosion hazard. Dispose of in

accordance with local authority requirements.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

FOOD GRADE SILICONE SPRAY NSF REG NO 136038 CAT H 1

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H304: May be fatal if swallowed and enters airways.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.