

**DRILLING & TAPPING LUBE** 

Page: 1

Compilation date: 23/08/2005

**Revision date:** 30/06/2016

Revision No: 5

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: DRILLING & TAPPING LUBE

Product code: DTL500
Synonyms: DTL500

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name: Specialised Aerosols Company Limited

Carr Green Lane Mapplewell

Barnsley

South Yorkshire

S75 6DY

**Tel:** 01226 387101 **Fax:** 01226 387100

Email: sales@specialised-aerosols.co.uk

## 1.4. Emergency telephone number

Emergency tel: 07836317118

## **Section 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Lact.: H362; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; -: H229;

Aquatic Chronic 2: H411

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. May cause harm to

breast-fed children. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

## Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated H362: May cause harm to breast-fed children.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS09: Environmental

**DRILLING & TAPPING LUBE** 

Page: 2





Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P263: Avoid contact during pregnancy/while nursing.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

## 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

# **Hazardous ingredients:**

#### ALKANES, C14-17, CHLORO

EINECS	CAS	PBT / WEL	CLP Classification	Percent
287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	10-30%
PROPANE				
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
ISOBUTANE				
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
BUTANE				
203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%

#### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**DRILLING & TAPPING LUBE** 

Page: 3

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

## Section 5: Fire-fighting measures

## 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up

to prevent the escape of liquid. Mark out the contaminated area with signs and prevent

access to unauthorised personnel.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

## **DRILLING & TAPPING LUBE**

Page: 4

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage

room must be impermeable to prevent the escape of liquids.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

#### Hazardous ingredients:

## **PROPANE**

## Workplace exposure limits:

## Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL				
UK	1800 mg/m3	7200 mg/m3	-					
ISOBUTANE								
UK	2400 mg/m3	9600 mg/m3	-	-				

BUTANE				
UK	1450 mg/m3	1810 mg/m3	-	-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

# 8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: Brown

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flammability limits %: lower: 0.8 upper: 9.0

Flash point°C: -10 VOC g/l: 128

**DRILLING & TAPPING LUBE** 

Page: 5

#### 9.2. Other information

Other information: No data available.

#### Section 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

Toxicity values: No data available.

#### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# Section 12: Ecological information

## 12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

**DRILLING & TAPPING LUBE** 

Page: 6

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Empty containers must not be burned because of explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

**Section 14: Transport information** 

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

**Special precautions:** No special precautions.

Tunnel code: D
Transport category: 2

**Section 15: Regulatory information** 

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

**Section 16: Other information** 

# **DRILLING & TAPPING LUBE**

Page: 7

# Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated H362: May cause harm to breast-fed children.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.