

SAFETY DATA SHEET

GREY PRIMER

Page 1

Issued: 23/08/2005

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: GREY PRIMER

Synonyms: GP500

GP400

Use / description of product: Extremely flammable. Irritant. Liquid. The regulatory information is dependent upon the concentration limit of the specific substance.

Company name: Specialised Aerosols Company Limited

Carr Green Lane

Mapplewell

Barnsley

South Yorkshire

S75 6DY

Tel: 01226 387101

Fax: 01226 387100

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: 2-BUTOXYETHANOL 1-10%

EINECS: 203-905-0 CAS: 111-76-2

[Xn] R20/21/22; [Xi] R36/38

- ACETONE 10-30%

EINECS: 200-662-2 CAS: 67-64-1

[F] R11; [Xi] R36; [Xi] R66; [-] R67

- BUTANE 10-30%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- XYLENE 1-10%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

3. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be vomiting. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

[cont...]

SAFETY DATA SHEET

GREY PRIMER

Inhalation: Nausea and stomach pain may occur. There may be vomiting. Drowsiness or mental confusion may occur. There may be loss of consciousness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Use; Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: 2-BUTOXYETHANOL
TWA 123 mg/m³

SAFETY DATA SHEET

GREY PRIMER

- ACETONE
TWA 1810 mg/m³ STEL 3620 mg/m³
- BUTANE
TWA 1450 mg/m³ STEL 1810 mg/m³
- XYLENE
TWA 220 mg/m³ STEL 441 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Grey

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flammability limits %: lower: 0.8

upper: 13.0

Flash point°C: -10

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong alkalis. Mineral Acids.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: 2-BUTOXYETHANOL

IVN RAT LD50 307 mg/kg

ORL MUS LD50 1230 mg/kg

ORL RAT LD50 470 mg/kg

- ACETONE

IVN RAT LD50 5500 mg/kg

ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

- XYLENE

ORL MUS LD50 2119 mg/kg

SAFETY DATA SHEET

GREY PRIMER

ORL RAT LD50 4300 mg/kg

SCU RAT LD50 1700 mg/kg

Chronic toxicity: Inhalation. Skin and/or eye contact.

Routes of exposure: May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach. Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to eyes. May cause chemical eye burns.

12. ECOLOGICAL INFORMATION**Other adverse effects:** Dangerous for the environment if discharged into watercourses.**13. DISPOSAL CONSIDERATIONS****Disposal of packaging:** Empty containers must not be burned because of explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID****UN no:** 1950**ADR Class:** 2**Shipping name:** AEROSOLS**Labelling:** 2.1**IMDG / IMO****UN no:** 1950**Class:** 2**EmS:** F-D,S-U**Marine pollutant:** .**Labelling:** 2.1**IATA / ICAO****UN no:** 1950**Class:** 2**Labelling:** 2.1**15. REGULATORY INFORMATION**

Hazard symbols: Extremely flammable.
Irritant.

SAFETY DATA SHEET

GREY PRIMER



Risk phrases: R12: Extremely flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe vapour.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37: Wear suitable gloves.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.
S51: Use only in well-ventilated areas.

Precautionary phrases: Contains methyl methacrylate. May produce an allergic reaction.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R36/38: Irritating to eyes and skin.
R11: Highly flammable.
R36: Irritating to eyes.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R12: Extremely flammable.
R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.