

WHITE GREASE

Page: 1

Compilation date: 24/08/05

Revision date: 04/01/2016

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WHITE GREASE

Product code: WG500 **Synonyms:** WG500

SGL16B

000769097045

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Specialised Aerosols Company Limited

Carr Green Lane

Mapplewell Barnsley

South Yorkshire

S75 6DY

Tel: 01226 387101 **Fax:** 01226 387100

Email: sales@specialised-aerosols.co.uk

1.4. Emergency telephone number

Emergency tel: 07836317118

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -:

H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

WHITE GREASE

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS09: Environmental







Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-151-9	64742-49-0	-	Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	30-50%
BUTANE				
203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
PROPANE				
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280 10-30	
ISOBUTANE				
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280 1-	

WHITE GREASE

Page: 3

ZINC OXIDE

-	1314-13-2	-	Aquatic Chronic 1: H410; Aquatic Acute	1-10%
			1: H400	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking

containers leak-side up to prevent the escape of liquid.

WHITE GREASE

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTANE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1450 mg/m3	1810 mg/m3	-	-
PROPANE				
UK	1800 mg/m3	7200 mg/m3	-	-
ISOBUTANE				
UK	2400 mg/m3	9600 mg/m3	-	-
ZINC OXIDE				
UK	5 mg/m3	10 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

WHITE GREASE

Page: 5

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Off-white

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Flammability limits %: lower: 0.8 upper: 9.0

Flash point°C: -10

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

WHITE GREASE

Page: 6

Hazardous ingredients:

ZINC OXIDE

IPR	RAT	LD50	240	mg/kg
ORL	MUS	LD50	7950	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis	
Skin corrosion/irritation	DRM	Hazardous: calculated	
STOT-single exposure	-	Hazardous: calculated	

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Empty containers must not be burned because of explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

WHITE GREASE

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H224: Extremely flammable liquid and vapour.
H229: Pressurised container: May burst if heated

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.

[final page]