STYLE REF: PM4002 STYLE NAME: JACKSON



INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 SRC | UK 3-16 (WHOLE SIZES) | COLOUR: BLACK

PROTECTIVE TOECAP AND MIDSOLE, JACKSON IS LIGHTWEIGHT AND DEVELOPED WITH PREMIUM MATERIALS INCLUDING AN ACTIV-STEP® SHOCK ABSORBING DUAL DENSITY PU OUTSOLE.























Upper Material

Water repellent smooth black leather

Protective Components

Protective steel toecap and stainless steel anti-penetration midsole

Lining Materials

Moisture wicking breathable mesh fabric lining

Scuff Cap and Outsole

Activ-Step® shock absorbing PU outsole

Footbed

Anti-fatigue EVA footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/03/2018

EC DECLARATION OF CONFORMITY



Head Office & Distribution Centre

Rock Fall UK Limited Unit 1 Major House Wimsey Way Alfreton, Derbyshire England. DE55 4LS

E: sales@rockfall.co.uk T: 01773 608616

www.rockfall.co.uk

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM

Declares that the PPE described hereafter;

PROMAN PM4002 JACKSON

Is in conformity with the provisions of PPE Regulation EU 2016/425 for Category II and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 17)

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD
MAJOR HOUSE, UNIT 1
WIMSEY WAY
ALFRETON
DERBYSHIRE, DE55 4LS
UNITED KINGDOM

Is identical to the PPE which is subject of EC certificate No **0075/2599/161/05/19/1532** Issued by:-

CTC GROUPE 4 RUE HERMANN FRENKEL 69367 LYON FRANCE

Is subject to the procedure set out in Article 17 of the PPE Regulation EU 2016/425 under the supervision of the notified body:

CTC GROUPE 4 RUE HERMANN FRENKEL 69367 LYON FRANCE

Signature:

Position: Director

Date: 15/05/2019













EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

PRO-MAN PM4002 JACKSON

 (ϵ)

Size 42

Rock Fall UK Major House Unit 1/3. Wimsey Way, Alfreton, Derbyshire, DE55 4LS,

United Kingdom

EN ISO 20345:2011 S3 SRC

12/2018

Certificate N°

0075/2599/161/05/19/1532

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer:

Rock Fall UK

Major House Unit 1/3, Wimsey Way, Alfreton, Derbyshire, DE55

4LS, United Kingdom

United Kingdom

Description

PPE Type:

a safety footwear

Product reference:

PRO-MAN PM4002 JACKSON

Article code:

Construction and material of outsole: Injection, PU/PU Sole

Pictures:





EN ISO 20345: 2011 Reference standard:

Classification: I

Category: S3

Size range: 36-51

Slip resistance: SRC

Toecap nature: Metallic

Insert nature: Metallic

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from MAY 2019

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by

Date of first issue: 13 May 2019

Maxence DREVET

End of validity date: 13 May 2024

Project Certification Manager





www.ctcgroupe.com

cemarking@ctcgroupe.com

Original CTC





TEST REPORT

Number: GZHT90166117

Tests Conducted (As Requested By The Applicant)

7 Internal Length Of Toe Cap (Toe Protection) (BS EN ISO20344: 2004 /A1:2007(5.3)):

			Requirement	Pass/Fail
Size 43	Left:	42 mm	Min. 40 mm	Pass
	Right:	42 mm	Min. 40 mm	Pass

Expended Uncertainty: 0.89 mm, with k = 2.22 at 95% confidence level

8 Impact Resistance (Toe Protection) (BS EN ISO20344: 2004 /A1:2007(5.4)):

			Requirement	Pass/Fail
Size 43	Left:	16.0 mm	Min. 14.5 mm	Pass
			(#)	
	Right:	16.0 mm	Min. 14.5 mm	Pass
			(#)	

Remark: # =In Addition, The Toecap Shall Not Develop Any Cracks On The Test Axis Which Go Through The Material, ie. Through Which Light Can Be Seen.

Expended Uncertainty: 0.49(Urel), with k=1.96 at 95% confidence level

9 Compression Resistance (Toe Protection) BS EN ISO20344: 2004 /A1:2007(5.5):

			Requirement	Pass/Fail Pass
Size 43	Left:	16.5 mm	Min. 14.5 mm	
	Right:	17.0 mm	Min. 14.5 mm	Pass

Expended Uncertainty: 0.13(Urel), with k= 1.96 at 95% confidence level

10 Outsole Slip Resistance (BS EN ISO 20344:2004/A1:2007 (5.18), SRC, 23 °C):

			Requir	rement	Pass/Fail
Size 43	Ceramic Tile/Sodium 1	Lauryl	1	-	:
-	Sulphate				
	Heel Part	0.45	Min.	0.28	Pass
	Flat Contact	0.47	Min.	0.32	Pass
	Steel Floor/Glycerol				
	Heel Part	0.17	Min.	0.13	Pass
	Flat Contact	0.20	Min.	0.18	Pass