



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/8

Duet - Clean Sense

Revision 3 Revision date 2012-12-24

| SECTION 1: Identification | of the substance/mixture and of the company/undertaking |
|------------------------------------|---|
| 1.1. Product identifier | |
| Product name | Duet - Clean Sense |
| 1.2. Relevant identified uses | of the substance or mixture and uses advised against |
| Product Use | [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC3] Air care products; |
| Description | Metered aerosols - Air Neutralizers. |
| 1.3. Details of the supplier of | the safety data sheet |
| Company | Rubbermaid Commercial Products LLC |
| Address | Newell Rubbermaid Europe Sàrl Chemin de Blandonnet 10 CH-1214 Vernier / Geneva / Switzerland |
| Web | www.rubbermaid.eu/contact |
| Telephone | +44 (0)8705 686 824 |
| Fax | +44 (0)2030 279 352 |
| Email | sds.CommercialProducts@newellco.com |
| Local Supplier | |
| Company | Newell Poland Services Sp. z o. o. |
| Address | 2 UI. Wybickiego Manieczki Brodnica 63-112 Poland |
| Web | www.rubbermaid.eu/contact |
| Telephone | +44 (0)8705 686 824 |
| Fax | +44 (0)2030 279 352 |
| 1.4. Emergency telephone n | umber |
| Emergency telephone number | +44 (0)8705 686 824 |
| Life and a discourse | Monday till Friday (08:30 - 17:00) |
| Intended use | |
| | Fragranced metered aerosol space sprays designed for use in proprietary automated dispensers. |
| Further information | |
| Informing Department | Technical Services Department. |
| SECTION 2: Hazards idea | ntification |
| 2.1. Classification of the sub | stance or mixture |
| 2.1.1. Classification - 1999/45/EC | F+; R12 Xi; R43 Symbols: F+: Extremely flammable. Xi: Irritant. |
| | |

Extremely flammable. May cause sensitisation by skin contact.

Main hazards

Revision 3 Revision date 2012-12-24

2.2. Label elements

The product is classified in accordance with 67/548/EEC.

For professional use only.

F+: Extremely flammable. Xi: Irritant.





Risk phrases

Symbols

Contains: Limonene.

R12 - Extremely flammable.

R43 - May cause sensitisation by skin contact.

Safety phrases

•

S2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S23 - Do not breathe gas/fumes/vapour/spray.

S24 - Avoid contact with skin.

S37 - Wear suitable gloves.

S51 - Use only in well-ventilated areas.

Precautionary Phrases

P10 - Contains hexyl cinnamal, citronellol, geraniol, acetyl cedrene, butylphenyl methylpropional.

May produce an allergic reaction.

Further information

Classification system

For mixtures, classification is in compliance with Regulation (EC) 1999/45. The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification |
|--------------------------------|--------------|------------|-----------|---------------------------------|-----------------|------------------------------------|
| Isobutane | 601-004-00-0 | 75-28-5 | 200-857-2 | | 40 - 50% | F+; R12 |
| Propane | 601-003-00-5 | 74-98-6 | 200-827-9 | | 10 - 20% | F+; R12 |
| Ethanol | 603-002-00-5 | 64-17-5 | 200-578-6 | | 10 - 20% | F; R11 |
| Isopropanol (Propan-2-ol) | 603-117-00-0 | 67-63-0 | 200-661-7 | | 1 - 10% | F; R11 Xi; R36 R67 |
| Dipropylene Glycol | | 110-98-5 | 203-821-4 | | 1 - 10% | |
| D-Limonene | 601-029-00-7 | 5989-27-5 | 227-813-5 | | 1 - 10% | R10 Xi; R38 R43 N; R50/53 |
| Linalool | | 78-70-6 | 201-134-4 | | 1 - 10% | Xi; R38 |
| 3,7-dimethyloctan-3-yl acetate | | 20780-48-7 | 244-033-0 | | 1 - 10% | |
| Hexyl Cinnamal | | 101-86-0 | 202-983-3 | | < 1% | Xi; R43 N; R50/53 |
| Butylphenyl methylpropional | | 80-54-6 | 201-289-8 | | < 1% | Xn; R22-62 Xi; R38-43 N; R51/53 |
| Geraniol | | 106-24-1 | 203-377-1 | | < 1% | Xi; R38-41-43 |
| Benzyl benzoate | 607-085-00-9 | 120-51-4 | 204-402-9 | | < 1% | Xn; R22 N; R51/53 |
| Citronellol | | 106-22-9 | 203-375-0 | | < 1% | |
| Acetyl Cedrene | | 32388-55-9 | 251-020-3 | | < 1% | Xi; R43 N; R50/53 |

Further information

Regulation (EU) 453/2010 - Substances in compliance with Regulation (EC) 1272/2008.



| Further information | |
|------------------------------------|---|
| | Isobutane - Flam. Gas 1: H220; GHS02; GHS04;. |
| | Propane - Flam. Gas 1: H220; GHS02; GHS04;. |
| | Ethanol - Flam. Liq. 2: H225; GHS02;. |
| | Isopropanol - Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; GHS07; GHS02;. |
| | Dipropylene Glycol - Skin Irr. 2: H315; Eye Irr. 2: H319; GHS07;. |
| | D-Limonene - Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 1: H410; GHS07; GHS02; GHS09;. |
| | Linalool - Skin Irrit. 2: H315; Eye Dam. 2: H319; GHS07;. |
| | 3,7-Dimethyloctan-3-yl acetate - Skin Irrit. 2: H315; Aquatic Chronic 2:H411; GHS07; GHS09;. Hexyl cinnamal - Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; GHS07; |
| | GHS09;. |
| | butylphenyl methylpropional - Acute Tox. 4: H302; Skin Irrit. 2: H315; Skin Sens. 1: H317; Repr. 2: |
| | H361; Aquatic Chronic 2: H411; GHS07; GHS09; GHS08;. |
| | Geraniol - Skin Irrit. 2: H315; Skin Sens. 1: H317; GHS07;. |
| | Benzyl benzoate - Acute Tox. 4: H302; Aquatic Chronic 2: H411; GHS07; GHS09;. |
| | Citronellol - Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 2: H319; GHS07;. |
| | Acetyl cedrene - Skin Sens. 1: H317; Aquatic Chronic 1: H410; GHS07; GHS09;. |
| Additional Information: | Full text for all Risk Phrases mentioned in this section are displayed in Section 16. |
| Description | Mixture of organic solvents, perfume and propane/iso-butane (propellant). |
| SECTION 4: First aid measu | res |
| 4.1. Description of first aid meas | sures |
| Inhalation | Move the exposed person to fresh air. |
| Eye contact | Rinse immediately with plenty of water for 15 minutes holding the eyelids open. |
| Skin contact | Wash off immediately with plenty of soap and water. |
| Ingestion | Rinse mouth thoroughly. DO NOT INDUCE VOMITING. |
| 4.2. Most important symptoms a | and effects, both acute and delayed |
| Inhalation | May cause dizziness and headache. |
| Eye contact | May cause irritation to eyes. |
| Skin contact | May cause irritation to skin. |
| 4.3. Indication of any immediate | medical attention and special treatment needed |
| Inhalation | If you feel unwell, seek medical advice (show the label where possible). |
| Eye contact | Seek medical attention. |
| Skin contact | Seek medical attention if irritation or symptoms persist. |
| Further information | |
| | In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). |
| SECTION 5: Firefighting mea | asures |
| 5.1. Extinguishing media | |
| | Carbon dioxide (CO2). Alcohol resistant foam. Do NOT use water jet. |
| 5.2. Special hazards arising from | • |
| , | Extremely flammable aerosol. Carbon oxides. Carbon dioxide (CO2). |
| 5.3. Advice for firefighters | |
| | Wear suitable respiratory equipment when necessary. |
| Further information | |
| | Cool fire exposed containers with waterspray. |
| SECTION 6: Assidantal ralas | |
| SECTION 6: Accidental release | 25C HICASUICS |



Revision 3 Revision date 2012-12-24

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective equipment. Evacuate personnel to a safe area. 6.2. Environmental precautions No environmental requirements. 6.3. Methods and material for containment and cleaning up Ensure adequate ventilation. Absorb liquid components with liquid binding material (sand, diatomite, acid binders, universal binders, sawdust). 6.4. Reference to other sections

See section 8 + 13 for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Wear suitable protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Ensure adequate ventilation of the working area.

Keep in a cool, dry, well ventilated area. Heat will increase pressure in sealed containers. Keep away from sources of ignition - No smoking. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not store with strong oxidising agents, Strong acids. Protect from heat and direct sunlight. Observe official regulations on storing packagings with pressurised containers.

7.3. Specific end use(s)

Air care products.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

| Ethanol | WEL 8-hr limit ppm: 1000 | WEL 8-hr limit mg/m3: 1920 |
|---------------------------|---------------------------|------------------------------|
| | WEL 15 min limit ppm: - | WEL 15 min limit mg/m3: - |
| Isopropanol (Propan-2-ol) | WEL 8-hr limit ppm: 400 | WEL 8-hr limit mg/m3: 999 |
| | WEL 15 min limit ppm: 500 | WEL 15 min limit mg/m3: 1250 |

Adopt best Manual Handling considerations when handling, carrying and dispensing.

Ensure adequate ventilation of the working area.

8.2. Exposure controls



8.2.1. Appropriate

engineering controls

8.2.2. Individual protection

measures

Eye / face protection Skin protection -

Handprotection Respiratory protection Avoid contact with eyes. Avoid contact with skin. Wear suitable gloves.

Not normally required.

Further information

Additional Information: Wash hands during breaks and at the end of the work.

SECTION 9: Physical and chemical properties

Revision 3 Revision date 2012-12-24

9.1. Information on basic physical and chemical properties

| State | Aerosol | | |
|------------------------------|-----------------------------------|--|--|
| Colour | cording to Product specification. | | |
| | Characteristic | | |
| Vapour pressure | 4.0 ± 0.5 bar | | |
| Vapour pressure Explosive | 1.8 - 19.0 vol % | | |
| Relative density | 0.62 - 0.632 | | |

SECTION 10: Stability and reactivity

| 1 | n | 1 | R | ea | ctiv | /it\ | , |
|---|---|---|---|----|------|------|---|
| | | | | | | | |

Stable under normal conditions.

10.2. Chemical stability

Will not decompose if stored and used as recommended.

10.3. Possibility of hazardous reactions

Strong oxidising agents.

10.4. Conditions to avoid

Store at temperatures above 50 °C. Heat, sparks and open flames.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Carbon oxides. Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| Respiratory or skin | May cause sensitisation by skin contact. |
|---------------------|--|
| sensitisation | |

11.1.4. Toxicological Information

| Ethanol | Oral Rat LD50: 6200 - 17800 | |
|-------------|-----------------------------------|-----------------------------------|
| | mg/kg | |
| Isopropanol | Inhalation Rat LC50/4 h: >20 mg/l | Oral Rat LD50: >5000 mg/kg |
| | Dermal Rabbit LD50: >5000 mg/kg | |

SECTION 12: Ecological information

12.1. Toxicity

| Ethanol | Algae IC50/72h: 5000 mg/l Fish LC50/96h: 11400 mg/l | | | |
|--|---|--|--|--|
| | | | | |
| | No data is available on this product. | | | |
| 12.2. Persistence and degradability | | | | |
| | Evaporates readily. | | | |
| 12.3. Bioaccumulative potential | | | | |
| | Does not bioaccumulate. | | | |
| 12.4. Mobility in soil | | | | |
| | Evaporates readily. | | | |
| 12.5. Results of PBT and vPvB assessment | | | | |
| | No data is available on this product. | | | |
| 12.6. Other adverse effects | | | | |
| | No data available. | | | |

Further information

Revision 3

| | Revision 3 |
|---------------------------------|---|
| | Revision date 2012-12-24 |
| Further information | T |
| | Do not allow product to enter drains. |
| SECTION 13: Disposal cons | iderations |
| General information | |
| | Dispose of in compliance with all local and national regulations. |
| Disposal methods | • |
| | Contact a licensed waste disposal company. |
| Disposal of packaging | , , , |
| | Dispose of in compliance with all local and national regulations. Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling. |
| SECTION 14: Transport info | rmation |
| Hazard pictograms | |
| | |
| | 2 |
| 14.1. UN number | |
| | UN1950 |
| 14.2. UN proper shipping name | |
| | AEROSOLS |
| 14.3. Transport hazard class(es | (s) |
| ADR/RID | 2 |
| Subsidiary risk | see SP63 |
| IMDG | 2 |
| Subsidiary risk | see SP63 |
| IATA | 2 |
| Subsidiary risk | see SP63 |
| 14.4. Packing group | |
| Packing group | - |
| 14.5. Environmental hazards | |
| Environmental hazards | No |
| Marine pollutant | No |
| ADR/RID | |
| Hazard ID | - |
| Tunnel Category | (D) |
| IMDG | |
| EmS Code | F-D S-U |
| IATA | |
| Packing Instruction (Cargo) | 203 |
| Maximum quantity | 150 kg |
| Packing Instruction | 203 |
| (Passenger) | |
| Maximum quantity | 75 kg |
| Further information | |
| Domarke | ADD. Goods are classified as "Limited Quantities" and are therefore except from ADD |

ADR - Goods are classified as "Limited Quantities" and are therefore excempt from ADR

Remarks

Revision 3 Revision date 2012-12-24

| Further information | | |
|--|--|--|
| regulations. Check local legislation for domestic transport. | | |
| Remarks | IMDG - Goods are classified as "Limited Quantities" and are therefore exempt from IMDG | |
| | regulations. Check local regulation for domestic transport. | |
| Remarks | "Limited Quantity". | |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

Aerosol product is manufactured in compliance with Commission Directive 2008/47/EC.

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No data is available on this product.

Further information

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

SECTION 16: Other information

Other information

- 1 Product Use.
- 2 2.1. Classification of the substance or mixture.
- 3 Further information.
- 4 Skin contact.
- 4 Skin contact.
- 8 Skin protection Handprotection.
- 8 Additional Information:.
- 9 9.1. Information on basic physical and chemical properties (State).
- 9 9.1. Information on basic physical and chemical properties (Colour).
- 9 9.1. Information on basic physical and chemical properties (Odour).
- 9 9.1. Information on basic physical and chemical properties (Relative density).
- 14 IMDG
- 14 Remarks.
- 15 Labelling.
- 15 Risk phrases.
- 15 Precautionary Phrases.
- 16 General information.

Data sources

Raw Material Data Sheets.

Exposure limits

Text of risk phrases in Section 3

R10 - Flammable

R11 - Highly flammable.

R12 - Extremely flammable.



| Other information | |
|----------------------|--|
| | R22 - Harmful if swallowed. |
| | R36 - Irritating to eyes. |
| | R38 - Irritating to skin. |
| | R41 - Risk of serious damage to eyes. |
| | R43 - May cause sensitisation by skin contact. |
| | R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic |
| | environment. |
| | R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic |
| | environment. |
| | R62 - Possible risk of impaired fertility. |
| | R67 - Vapours may cause drowsiness and dizziness. |
| General information | |
| | Additional information in compliance with Regulation (EC) 1272/2008. |
| | H220 - Extremely flammable gas. |
| | H225 - Highly flammable liquid and vapour. |
| | H226 - Flammable liquid and vapour. |
| | H302 - Harmful if swallowed. |
| | H315 - Causes skin irritation. |
| | H317 - May cause an allergic skin reaction. |
| | H319 - Causes serious eye irritation. |
| | H336 - May cause drowsiness or dizziness. |
| | H361 - Suspected of damaging fertility or the unborn child . |
| | H400 - Very toxic to aquatic life. |
| | H410 - Very toxic to aquatic life with long lasting effects. |
| | H411 - Toxic to aquatic life with long lasting effects. |
| Further information | |
| | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, |
| | storage and handling of the product. This information is correct to the best of our knowledge and |
| | belief at the date of publication however no guarantee is made to its accuracy. This information |
| | relates only to the specific material designated and may not be valid for such material used in |
| | combination with any other materials or in any other process. |
| | *. |
| Informing Department | Technical Services Department. |
| 0 - 1 | I Programme Transfer of the Programme Transf |







SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/8

Duet - Cool Breeze

| SECTION 1: Identification | of the substance/mixture and of the company/undertaking |
|------------------------------------|---|
| 1.1. Product identifier | |
| Product name | Duet - Cool Breeze |
| 1.2. Relevant identified uses | of the substance or mixture and uses advised against |
| Product Use | [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC3] Air care products; |
| Description | Metered aerosols - Air Neutralizers. |
| 1.3. Details of the supplier of | f the safety data sheet |
| Company | Rubbermaid Commercial Products LLC |
| Address | Newell Rubbermaid Europe Sàrl Chemin de Blandonnet 10 CH-1214 Vernier / Geneva / Switzerland |
| Web | www.rubbermaid.eu/contact |
| Telephone | +44 (0)8705 686 824 |
| Fax | +44 (0)2030 279 352 |
| Email | sds.CommercialProducts@newellco.com |
| Local Supplier | |
| Company | Newell Poland Services Sp. z o. o. |
| Address | 2 UI. Wybickiego Manieczki Brodnica |
| | 63-112 Poland |
| Web | www.rubbermaid.eu/contact |
| Telephone | +44 (0)8705 686 824 |
| Fax | +44 (0)2030 279 352 |
| 1.4. Emergency telephone n | umber |
| Emergency telephone number | +44 (0)8705 686 824 |
| | Monday till Friday (08:30 - 17:00) |
| Intended use | |
| | Fragranced metered aerosol space sprays designed for use in proprietary automated dispensers. |
| Further information | |
| Informing Department | Technical Services Department. |
| SECTION 2: Hazards ide | ntification |
| 2.1. Classification of the sub | stance or mixture |
| 2.1.1. Classification - 1999/45/EC | F+; R12 Symbols: F+: Extremely flammable. |
| Main hazards | Extremely flammable. |

Revision 4
Revision date 2012-12-23

2.2. Label elements

The product is classified in accordance with 67/548/EEC.

For professional use only.

F+: Extremely flammable.



Risk phrases

Symbols

Safety phrases

R12 - Extremely flammable.

S2 - Keep out of the reach of children.

S16 - Keep away from sources of ignition - No smoking.

S23 - Do not breathe gas/fumes/vapour/spray.

S51 - Use only in well-ventilated areas.

Precautionary Phrases

P10 - Contains hexyl cinnamal, acetyl cedrene, tetramethyl acetyloctahydronaphthalenes, hexyl salicylate. May produce an allergic reaction.

Further information

Classification system

For mixtures, classification is in compliance with Regulation (EC) 1999/45. The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification |
|--|--------------|------------|-----------|---------------------------------|-----------------|----------------------|
| Isobutane | 601-004-00-0 | 75-28-5 | 200-857-2 | | 40 - 50% | F+; R12 |
| Propane | 601-003-00-5 | 74-98-6 | 200-827-9 | | 10 - 20% | F+; R12 |
| Ethanol | 603-002-00-5 | 64-17-5 | 200-578-6 | | 10 - 20% | F; R11 |
| Isopropanol (Propan-2-ol) | 603-117-00-0 | 67-63-0 | 200-661-7 | | 1 - 10% | F; R11 Xi; R36 R67 |
| Dipropylene Glycol | | 110-98-5 | 203-821-4 | | 1 - 10% | |
| 2,6-dimethyloct-7-en-2-ol | | 18479-58-8 | 242-362-4 | | 1 - 10% | Xi; R38 |
| Linalyl acetate | | 115-95-7 | 204-116-4 | | < 1% | Xi; R38 N; R51/53 |
| Hexyl Cinnamal | | 101-86-0 | 202-983-3 | | < 1% | Xi; R43 N; R50/53 |
| Hexyl Salicylate | | 6259-76-3 | 228-408-6 | | < 1% | Xi; R38-43 N; R50/53 |
| Acetyl Cedrene | | 32388-55-9 | 251-020-3 | | < 1% | Xi; R43 N; R50/53 |
| Beta-Ionone | | 14901-07-6 | 238-969-9 | | < 1% | N; R51/53 |
| 4-Tertiary-butylcyclohexyl acetate | | 32210-23-4 | 250-954-9 | | < 1% | N; R51/53 |
| tetramethyl Acetyloctahydronaphthalenes | | 54464-57-2 | 259-174-3 | | < 1% | Xi; R43 N; R51/53 |

Further information

Regulation (EU) 453/2010 - Substances in compliance with Regulation (EC) 1272/2008.

Isobutane - Flam. Gas 1: H220; GHS02; GHS04;. Propane - Flam. Gas 1: H220; GHS02; GHS04;.

Ethanol - Flam. Liq. 2: H225; GHS02;.

Isopropanol - Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; GHS07; GHS02;.

Dipropylene Glycol - Skin Irr. 2: H315; Eye Irr. 2: H319; GHS07;.

2,6-Dimethyloct-7-en-2-ol - Skin Irrit. 2: H315; Eye Dam. 2: H319; GHS07;.



| | Revision date 2012-12- |
|-----------------------------------|--|
| Further information | |
| | Linalyl acetate - Skin Irrit. 2: H315; Eye Dam. 2: H319; GHS07;. |
| | Hexyl cinnamal - Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; GHS07; GHS09;. |
| | Hexyl salicylate - Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Dam. 2: H319; Aquatic Chronic 1: H410; GHS07; GHS09;. |
| | 4-Tertiary-buttylcyclohexyl acetate - Aquatic Chronic 2: H411; GHS09;. Beta-ionone - Aquatic Chronic 2: H411; GHS09;. |
| | Acetyl cedrene - Skin Sens. 1: H317; Aquatic Chronic 1: H410; GHS07; GHS09;. |
| | Tetramethyl acetyloctahydronaphthalenes - Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquat. Chroni 2: H411; GHS07; GHS09;. |
| Additional Information: | Full text for all Risk Phrases mentioned in this section are displayed in Section 16. |
| Description | Mixture of organic solvents, perfume and propane/iso-butane (propellant). |
| SECTION 4: First aid measu | ıres |
| 1.1. Description of first aid mea | sures |
| nhalation | Move the exposed person to fresh air. |
| Eye contact | Rinse immediately with plenty of water for 15 minutes holding the eyelids open. |
| Skin contact | Wash off immediately with plenty of soap and water. |
| Ingestion | Rinse mouth thoroughly. DO NOT INDUCE VOMITING. |
| I.2. Most important symptoms | and effects, both acute and delayed |
| nhalation | May cause dizziness and headache. |
| Eye contact | May cause irritation to eyes. |
| Skin contact | May cause irritation to skin. |
| I.3. Indication of any immediat | e medical attention and special treatment needed |
| nhalation | If you feel unwell, seek medical advice (show the label where possible). |
| Eye contact | Seek medical attention. |
| Skin contact | Seek medical attention if irritation or symptoms persist. |
| Further information | 1 |
| | In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). |
| SECTION 5: Firefighting me | easures |
| 5.1. Extinguishing media | |
| | Carbon dioxide (CO2). Alcohol resistant foam. Do NOT use water jet. |
| 5.2. Special hazards arising fro | · |
| | Extremely flammable aerosol. Carbon oxides. Carbon dioxide (CO2). |
| 5.3. Advice for firefighters | |
| • | Wear suitable respiratory equipment when necessary. |
| Further information | |
| | Cool fire exposed containers with waterspray. |
| SECTION 6: Accidental rele | ase measures |
| 6.1. Personal precautions, prot | ective equipment and emergency procedures |
| | Wear suitable protective equipment. Evacuate personnel to a safe area. |
| 6.2. Environmental precautions | |
| | No environmental requirements. |
| 6.3. Methods and material for o | |
| | Ensure adequate ventilation. Absorb liquid components with liquid binding material (sand, |
| | I are a serial s |



Revision Revision date 2012-12-23

6.3. Methods and material for containment and cleaning up

diatomite, acid binders, universal binders, sawdust)

6.4. Reference to other sections

See section 8 + 13 for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Wear suitable protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Ensure adequate ventilation of the working area.

Keep in a cool, dry, well ventilated area. Heat will increase pressure in sealed containers. Keep away from sources of ignition - No smoking. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not store with strong oxidising agents, Strong acids. Protect from heat and direct sunlight. Observe official regulations on storing packagings with pressurised containers.

7.3. Specific end use(s)

Air care products.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

| Ethanol | WEL 8-hr limit ppm: 1000 WEL 8-hr limit mg/m3: 1920 | |
|---------------------------|---|------------------------------|
| | WEL 15 min limit ppm: - | WEL 15 min limit mg/m3: - |
| Isopropanol (Propan-2-ol) | WEL 8-hr limit ppm: 400 | WEL 8-hr limit mg/m3: 999 |
| | WEL 15 min limit ppm: 500 | WEL 15 min limit mg/m3: 1250 |

Adopt best Manual Handling considerations when handling, carrying and dispensing.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection

measures

Avoid contact with eyes.

Skin protection -Handprotection

Eye / face protection

Wash hands after handling the product.

Respiratory protection

Not normally required.

Further information

Additional Information:

Wash hands during breaks and at the end of the work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State Colour Aerosol

According to Product specification.

Odour Vapour pressure

Characteristic 4.0 ± 0.5 bar

Relative density **Explosive**

0.62 - 0.632 1.8 - 19.0 vol%

SECTION 10: Stability and reactivity

10.1. Reactivity

Revision 4
Revision date 2012-12-23

Disposal of packaging

Empty containers can be sent for disposal or recycling.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

| ADR/RID | 2 |
|-----------------|----------|
| Subsidiary risk | see SP63 |
| IMDG | 2 |
| Subsidiary risk | see SP63 |
| IATA | 2 |
| Subsidiary risk | see SP63 |

14.4. Packing group

Packing group

14.5. Environmental hazards

| Environmental hazards | |
|-----------------------|----|
| Marine pollutant | No |

ADR/RID

| Hazard ID | - |
|-----------------|-----|
| Tunnel Category | (D) |

IMDG

| EmS Code | F-D S-U |
|----------|---------|
| | |

IATA

| Packing Instruction (Cargo) | 203 |
|-----------------------------|--------|
| Maximum quantity | 150 kg |
| Packing Instruction | 203 |
| (Passenger) | |
| Maximum quantity | 75 kg |

Further information

| Remarks | ADR - Goods are classified as "Limited Quantities" and are therefore excempt from ADR |
|---------|--|
| | regulations. Check local legislation for domestic transport. |
| Remarks | IMDG - Goods are classified as "Limited Quantities" and are therefore exempt from IMDG |
| | regulations. Check local regulation for domestic transport. |
| Remarks | "Limited Quantity". |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| Regulations | Aerosol product is manufactured in compliance with Commission Directive 2008/47/EC. |
|-------------|---|
| | COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No |



Revision 4
Revision date 2012-12-23

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No data is available on this product.

Further information

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

SECTION 16: Other information

Other information

| Revision The Control of the Control | his document differs from the previous | version in the following areas:. |
|---|--|----------------------------------|
|---|--|----------------------------------|

- 3 Further information.
- 4 Eye contact.
- 4 Skin contact.
- 4 Eye contact.
- 4 Skin contact.
- 8 Additional Information:.
- 11 Skin corrosion/irritation.
- 11 Respiratory or skin sensitisation.
- 15 Precautionary Phrases.
- 16 General information.

Data sources

Raw Material Data Sheets.

Exposure limits.

Text of risk phrases in Section 3

- R11 Highly flammable.
- R12 Extremely flammable.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R43 May cause sensitisation by skin contact.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 - Vapours may cause drowsiness and dizziness.

General information

Additional information in compliance with Regulation (EC) 1272/2008.

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.



| General information | | |
|----------------------|--|--|
| | H411 - Toxic to aquatic life with long lasting effects. | |
| Further information | | |
| | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. *. | |
| Informing Department | Technical Services Department. | |

