

Vital 124

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 30.5
- **Thickness (mm)** 0.35
- **Wrist** Straight cuff
- **Colour/Color** Yellow
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5

KPT

0010X

Legends

| ANSI | CUT RESISTANCE | | |
|------------|----------------|-------------|-------------|
| A1 | A1 ≥ 200 G | A4 ≥ 1500 G | A7 ≥ 4000 G |
| | A2 ≥ 500 G | A5 ≥ 2200 G | A8 ≥ 5000 G |
| CUT | A3 ≥ 1000 G | A6 ≥ 3000 G | A9 ≥ 6000 G |

| EN 511 | COLD HAZARDS | | |
|--------|--------------------|--------------------|----------------------------|
| | PERFORMANCE LEVELS | | |
| | 0-4 | 0-4 | 0 or 1 |
| | | Water permeability | Contact cold resistance |
| | | | Convective cold resistance |

| EN 407 | THERMAL RISKS | | |
|--------|--------------------|--|---|
| | Heat and fire | | |
| | PERFORMANCE LEVELS | | |
| | 0-4 | 0-4 | 0-4 0-4 0-4 0-4 |
| | | Resistance to large quantities of molten metal | Resistance to small drops of molten metal |
| | | Radiant heat resistant | Convective heat resistance |
| | | Contact heat resistance | Burning behaviour |

| PROTECTION FROM PESTICIDES | | |
|----------------------------|-----------|-----------|
| ISO 18889 | ISO 18889 | ISO 18889 |
| | | |
| G1 | G2 | GR |

| MICRO-ORGANISMS | |
|------------------------------------|---|
| EN ISO 374-5 | EN ISO 374-5 |
| | |
| Protection against bacteria, fungi | Protection against bacteria, fungi, virus |
| | VIRUS |

| EN 388 | MECHANICAL HAZARDS | | |
|--------|--------------------|----------------------|---------------------------------------|
| | PERFORMANCE LEVELS | | |
| | 0-4 | 0-5 | 0-4 0-4 A-F (P) |
| | | Blade cut resistance | Tear resistance |
| | | Puncture resistance | Cut resistance according to ISO 13997 |
| | | | Impact protection |
| | | | Abrasion resistance |

| CHEMICAL RISKS | | |
|--------------------|-------------------------|--------------|
| EN ISO 374-1 | EN ISO 374-1 | EN ISO 374-1 |
| Type A | Type B | Type C |
| | | |
| U V W X Y Z | X Y Z | |
| A Methanol | J n-Heptane | |
| B Acetone | K Sodium hydroxide 40% | |
| C Acetonitrile | L Sulphuric acid 96% | |
| D Dichloromethane | M Nitric acid 65% | |
| E Carbon Disulfide | N Acetic acid 99% | |
| F Toluene | O Ammonia 25% | |
| G Diethylamine | P Hydrogen peroxide 30% | |
| H Tetrahydrofurane | S Hydrofluoric acid 40% | |
| I Ethyl acetate | T Formaldehyde 37% | |

| RADIOACTIVE CONTAMINATION |
|---------------------------|
| EN 421 |
| |

| ELECTROSTATIC DISCHARGE PROTECTION |
|------------------------------------|
| EN 16350 |
| |

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

SPECIFIC ADVANTAGES

- Excellent dexterity from the suppleness of natural latex
- Good resistance
- Comfortable cotton flock-lining

MAIN FIELDS OF USE

Mechanical industry

- Assembly of small, oil and grease free parts

Food industry

- Common cleaning Tasks

Local Authorities (Cleaning)

- Handling household detergents

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitised to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in contact with a solvent (alcohol, etc...) : rub over with a dry cloth.
- in contact with acids or alkalies: thoroughly rinse the gloves under running water, and rub over with a dry cloth.
- Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/03/18/0525
- **Issued by the notified body nr** : 0075 - C.T.C – 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS