

WIRE ROPE SPRAY WITH PTFE

Page: 1

Compilation date: 10/02/2014

Revision date: 01/04/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WIRE ROPE SPRAY WITH PTFE

Product code: WRS500

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	Specialised Aerosols Company Limited
	Carr Green Lane
	Mapplewell
	Barnsley
	South Yorkshire
	S75 6DY
Tel:	01226 387101
Fax:	01226 387100
Email:	sales@specialised-aerosols.co.uk

1.4. Emergency telephone number

Emergency tel: 07836317118

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; STOT SE 3: H336

Most important adverse effects: Extremely flammable aerosol. Causes skin irritation. May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements:	H222: Extremely flammable aerosol.
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H412: Harmful to aquatic life with long lasting effects.
Hazard pictograms:	GHS07: Exclamation mark

GHS02: Flame



WIRE ROPE SPRAY WITH PTFE

Signal words:WarningPrecautionary statements:P264: Wash hands thoroughly after handling.P273: Avoid release to the environment.P270: Wear protective gloves/protective clothing/eye protection/face protection.P302+352: IF ON SKIN: Wash with plenty of water/.P302+352: IF ON SKIN: Wash with plenty of water/.P311: Specific treatment (see instructions on this label).P332+313: If skin irritation occurs: Get medical attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT - REACH registered number(s): 01-2119475514-35-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-151-9	64742-49-0	-	Asp. Tox. 1: H304; Flam. Liq. 1: H224;	10-30%
			Skin Irrit. 2: H315; Aquatic Chronic 2: H411	

BUTANE

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
PROPANE				
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
ISOBUTANE				
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
BASEOIL - UN	ISPECIFIED - DI	STILLATES (PETROLEUM), HYDROT	REATED HEAVY NAPHTHENIC	
265-155-0	64742-52-5	-	-	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

Page: 2

WIRE ROPE SPRAY WITH PTFE

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

WIRE ROPE SPRAY WITH PTFE

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTANE

Workplace exposure limits:

State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL UK 1450 mg/m3 1810 mg/m3

Respirable dust

PROPANE

UK	1800 mg/m3	7200 mg/m3	-	-
ISOBUTANE				
UK	2400 mg/m3	9600 mg/m3	-	_

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.	
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.	
Hand protection:	Protective gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Protective clothing.	

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:AerosolColour:Typical.

Odour: Characteristic odour

Flammability limits %: lower: 3.0

upper: 18.6

WIRE ROPE SPRAY WITH PTFE

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

WIRE ROPE SPRAY WITH PTFE

Page: 6

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Marine pollutant: No

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

WIRE ROPE SPRAY WITH PTFE

Page: 7

15.2. Chemical Safety Assessment

Section 16: Other information

Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	2015/830.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.	
	H222: Extremely flammable aerosol.	
	H224: Extremely flammable liquid and vapour.	
	H304: May be fatal if swallowed and enters airways.	
	H315: Causes skin irritation.	
	H336: May cause drowsiness or dizziness.	
	H411: Toxic to aquatic life with long lasting effects.	
	H412: Harmful to aquatic life with long lasting effects.	
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and	
	shall be used only as a guide. This company shall not be held liable for any damage resulting	
	from handling or from contact with the above product.	